

## PRODUCT DATA SHEET

# Sika® Reemat Lite

### Glass fibre mat reinforcement

#### DESCRIPTION

Sika® Reemat Lite is a glass fibre mat reinforcement for Sikagard® Hygienic Coating systems

#### USES

- Reinforcement for Sikagard® Hygienic Coating Systems
- Reinforcement for Sikagard® Hygienic Coating detailing
- For new construction and refurbishment projects

#### CHARACTERISTICS / ADVANTAGES

- Easy and quick application
- Easy to adjust to complicated details
- Ensures the correct thickness of the base coat
- Enhance the crack-bridging properties of the system
- Enhance mechanical properties of the system

#### PRODUCT INFORMATION

<b>Composition</b>	Random glass fibre matting
<b>Packaging</b>	Rolls: 1m wide by 50m long
<b>Appearance / Colour</b>	White
<b>Shelf life</b>	Product does not expire if correctly stored
<b>Storage conditions</b>	The product must be stored properly in original, unopened and undamaged sealed packaging, flat and wrinkle free, in dry conditions at temperatures between +5 °C and +35 °C.
<b>Density</b>	~30 g / m <sup>2</sup>

#### SYSTEMS

<b>Systems</b>	For detailed information regarding system build-ups, please refer to the System or Product Data Sheet of the relevant Sikagard® Hygienic Coating System.
----------------	--

## BASIS OF PRODUCT DATA

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

## IMPORTANT CONSIDERATIONS

Limitations will be dictated by the individual Sikagard® Hygienic Coating being used – Please consult relevant Product Datasheet / System Datasheet.

## ECOLOGY, HEALTH AND SAFETY

REGULATION (EC) NO 1907/2006 - REACH

## APPLICATION INSTRUCTIONS

### APPLICATION

Prior the application of the Sikagard® Hygienic Coating System the priming coat if used must have cured for the appropriate Waiting Time / Overcoating (please refer to the PDS of the appropriate primer). Damageable areas (handrails etc.) have to be protected with tape or plastic wrapping.

Sika® Reemat Lite is applied in combination with Sikagard® Hygienic Coatings.

Apply first coat of Sikagard® Hygienic Coating with a consumption rate according to the PDS of the relevant hygienic coating system. Work only so far in advance that the material stays liquid.

Roll out the Sika® Reemat Lite and ensure that there are no bubbles or creases. Overlapping of Sika® Reemat Lite must be minimum 5 cm and ensure overlaps are sufficiently wet to bond.

The roller may require only a little extra material to remain wet but no further significant material needs to be added at this stage.

After the coat as had the appropriate Waiting Time / Overcoating continue with subsequent coats as per the relevant Sikagard® Hygienic Coating Datasheet / System Datasheet.

## LOCAL RESTRICTIONS

Please note that as a result of specific local regulations the declared data for this product may vary from country to country. Please consult the local Product Data Sheet for the exact product data.

## LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its

### PRODUCT DATA SHEET

Sika® Reemat Lite

December 2020, Version 03.01

020816110010000009

**BUILDING TRUST**



products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

**Sika Iraq (Sika Trading L.L.C.)**

Erbil / Baghdad / Basra

Tel: +96 477 303 74451

info@iq.sika.com

iq.sika.com

SikaReematLite-en-IQ-(12-2020)-3-1.pdf

**PRODUCT DATA SHEET**

Sika® Reemat Lite

December 2020, Version 03.01

020816110010000009

